



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/732,722	12/10/2003	Bill Eaton	200207091-1	2011

22879 7590 04/17/2007
HEWLETT PACKARD COMPANY
P O BOX 272400, 3404 E. HARMONY ROAD
INTELLECTUAL PROPERTY ADMINISTRATION
FORT COLLINS, CO 80527-2400

EXAMINER

MISIURA, BRIAN THOMAS

ART UNIT	PAPER NUMBER
----------	--------------

2111

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	04/17/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary	Application No. 10/732,722	Applicant(s) EATON, BILL	
	Examiner Brian T. Misiura	Art Unit 2111	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 10 December 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-48 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-48 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 10 December 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>12/10/2003</u> | 6) <input type="checkbox"/> Other: _____ |

Detailed Action

Claim Objections

The following is a quotation of the fourth paragraph of 35 U.S.C. 112:

Subject to the following paragraph, a claim in dependent form shall contain a reference to a claim previously set forth and then specify a further limitation of the subject matter claimed. A claim in dependent form shall be construed to incorporate by reference all the limitations of the claim to which it refers.

Claims 10, 22, and 23, are objected to under 37 CFR 1.75(c), as being of improper dependent form for failing to further limit the subject matter of a previous claim. Applicant is required to cancel the claim(s), or amend the claim(s) to place the claim(s) in proper dependent form, or rewrite the claim(s) in independent form. By claiming the system of Claim 1 is comprised within a (printing device or ASIC) fails to further limit Claim 1.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 10, 22, and 23, are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. As claimed, it is unclear as to how the 'multiple integrated circuit control system' and the ('printing device' and 'application-specific integrated circuit (ASIC)) are utilized in combination with each other.

Claim 36 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. The following limitation is unclear: "communicating a control parity bit from the multiple integrated circuit control for

Art Unit: 2111

the unique target identifier and for control data error checking at the identified integrated circuit". It is unclear if the limitation was meant to convey that the control parity bit is communicated to verify a correct unique target identifier, or if the control parity bit is meant to be sent from the multiple integrated circuit to the unique target identifier. The limitation will be interpreted as though the control parity bit is to be sent from the multiple integrated circuit to the unique target identifier in order for control data error checking to take place.

Claims 37-42 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. It is unclear as to how the claimed multiple computer-readable media are used in this invention. The Examiner will interpret computer-readable media as a single computer-readable media comprising 1 or more of the same computer-readable media which are utilized as 1, or more than one computer-readable media used together as a single computer-readable media.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-9, 11, 12, 15-21, 24, 26-34, and 37-48 are rejected under 35 U.S.C. 102(b) as being anticipated by Schutte U.S. Patent No. 6,092,138.

Per Claims 1 and 24, Schutte discloses:

Art Unit: 2111

- a multiple integrated circuit controller configured to initiate and control data transactions between the multiple integrated circuit controller and integrated circuits (figure 1 numerals 10a-e represent stations, any of the stations can become a master station, which would then assume the role as the 'integrated circuit controller' – column 6 lines 11-22);
- a data link configured to communicate the data transactions between the multiple integrated circuit controller and one or more of the integrated circuits (column 3 line 66 – column 4 line 9, figure 1 numeral 12a-b, SDA and SDAH represent data buses), the multiple integrated circuit controller including a first push-pull driver to drive the data transactions (column 14, lines 43-54, figure 6 numerals 66, 67, and SDA);
- and a clock signal link configured to communicate a clock signal generated by the multiple integrated circuit controller to the integrated circuits (column 3 line 66 – column 4 line 9, figure 1 numeral 12a-b, SCL and SCLH represent clock buses), the multiple integrated circuit controller including a second push-pull driver to drive the clock signal (column 14 lines 55-63, figure 6 numerals 63 and 64).

Per Claim 2, Schutte discloses wherein the data link and the clock signal link form a two-wire control data bus (column 1 lines 22-26, figure 1 – the I2C bus is that of a two-wire bus)

Per Claims 3, 15, 26, Schutte discloses wherein the data link is further configured to communicate write data from the multiple integrated circuit controller to one or more of the integrated circuits (column 6 lines 11-16, figure 1 – the master station utilizes the read/write bit to indicate what type of data communication will take place any of the stations can act as a master and when the master can communicate both read and write transactions with any of the other stations).

Art Unit: 2111

Per Claims 4, 16, 27, Schutte discloses wherein the data link is further configured to communicate read data from one or more of the integrated circuit to the multiple integrated circuit controller (column 6 lines 11-16, figure 1 – the master station utilizes the read/write bit to indicate what type of data communication will take place).

Per Claims 5, 17, 28, Schutte discloses wherein the multiple integrated circuit controller is further configured to control a write data transaction from the multiple integrated circuit controller to a first integrated circuit via the data link, and control a read data transaction from a second integrated circuit to the multiple integrated circuit controller via the data link (column 6 lines 11-22, figure 1 – any of the stations can act as a master and when the master can communicate both read and write transactions with any of the other stations).

Per Claims 6, 18, 29, 39, and 45, Schutte discloses wherein the clock signal link is further configured to communicate a continuous clock signal generated by the multiple integrated circuit controller to one or more of the integrated circuits (figure 5 – SCLk takes the form of a continuous clock signal during high speed mode (Hs-mode)).

Per Claims 7, 19, 30, 40, and 46, Schutte discloses wherein the clock signal link is further configured to communicate a pulsed clock signal generated by the multiple integrated circuit controller to one or more of the integrated circuits (figure 5 – SCLk takes the form of a pulsed clock signal during the first 9 clock signals).

Per Claims 8, 20, 31, 41, and 47, Schutte discloses wherein the data link is further configured to communicate error check data between the multiple integrated circuit controller and one or more of the integrated circuits (column 6 lines 35-50, figure 1 – the acknowledge bit qualifies as error check data).

Art Unit: 2111

Per Claims 9, 21, 32, 33, 42, and 48, Schutte discloses

- wherein the multiple integrated circuit controller is further configured to communicate a unique target identifier via the data link to initiate a data transaction with an integrated circuit that has an address identified by the unique target identifier (column 6 line 11-22, figure 1 – if the address supplied by the master station matches that of a slave station then that slave station responds to the communication accordingly);
- in an event that the data transaction is a write data transaction, the data link is further configured to communicate the data from the multiple integrated circuit controller to the identified integrated circuit; and in an event that the data transaction is a read data transaction, the data link is further configured to communicate the data from the identified integrated circuit to the multiple integrated circuit controller (column 6 lines 11-24, figure 1 - the master station utilizes the read/write bit to indicate what type of data communication will take place; any of the stations can act as a master and when acting as the master can communicate both read and write transactions with any of the other stations).

Per Claim 11, Schutte discloses:

- a clock signal output configured to communicate a clock signal to integrated circuits via a first data link of a data bus (column 12 lines 44-58, figure 5);
- a first push-pull driver configured to drive the clock signal on the first data link (column 14 lines 55-63, figure 6 numerals 63 and 64);
- a data input/output configured to communicate data between the multiple integrated circuit control and one or more of the integrated circuits via a second data link of the data bus (column 6 lines 11-22, figure 1);
- and a second push-pull driver configured to drive the data on the second data link (column 14, lines 43-54, figure 6 numerals 66, 67, and SDA).

Art Unit: 2111

Per Claims 12 and 34, Schutte discloses the multiple integrated circuit control as recited in claim 11 implemented as a single-ended interface control circuit (the system of Schutte is believed to be that of a single-ended system based fact well known in the art that the I2C transmission protocol uses single-ended signaling (this argument is further supported by the included document titled "Single-ended signaling"). Additionally, the lack of Schutte distinctly disclosing the system as using a differential signaling method also supports the reasoning for the signaling of Schutte to be that of single-ended).

Per Claims 37 and 38, Schutte discloses all the limitations presented in this claim. Regarding the computer readable media, Schutte discloses a control/function unit 61 that is coupled to both the data and clock bus drivers, therefore overseeing the communications occurring on those buses. The remaining limitations have been previously rejected with respect to Claims 1, 3, and 4. Please refer to Claims 1, 3, and 4 for explanation of rejection.

Per Claims 43 and 44, the limitations of these claims have already been rejected with respect to Claims 1, 3, and 4. Please refer back to the rejection of those claims for explanation.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2111

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Claims 10 and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Schutte U.S. Patent No. 6,092,138 in view of Kawamoto U.S. Patent No. 6,967,744.

Per Claims 10 and 22, Schutte does not distinctly disclose the I2C controller as being located within a printing device.

- However, it would have been obvious to one having ordinary skill in the art at the time of the applicants claimed invention to incorporate the I2C protocol setup of Schutte into a printing device in order to benefit from the advantages that an I2C bus has over other conventional bus systems. Motivation for the combination can be seen in Kawamoto, where an I2C controller and system is present within an image processing apparatus (column 3 lines 1-15, column 4 lines 15-31, and figure 1).

Claim 13, 14, 25, and 35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Schutte U.S. Patent No. 6,092,138 in view of Lattice Semiconductor Corporation, "Differential Signaling" – dated May 2001 (hereafter referred to as Lattice).

Per Claims 13 and 35, Schutte does not distinctly disclose the multiple integrated circuit control as recited in claim 11 implemented as a low voltage differential signaling (LVDS) interface control circuit.

- However, it would have been obvious to one having ordinary skill in the art at the time of the applicants claimed invention to implement the system of Schutte as that of a LVDS. This combination is simply the alternative to using single-ended signaling and is a matter of design choice. Lattice provides several scenarios when using differential signaling would be beneficial. A few of the scenarios include: when the signals are small, when there is a lot of noise, when signals need to run over a distance, and when the signal source is balanced to begin with (page 4). Based on the advantages of using differential signaling as outlined by Lattice, it would have been obvious to implement the system of Schutte as that of a LVDS.

Per Claims 14, 25, Schutte does not disclose a multiple integrated circuit control as recited in claim 11 implemented as a low voltage differential signaling interface control circuit, wherein: the first data link is a differential clock signal link configured to communicate the clock signal as a low voltage differential clock signal; and the second data link is a differential data link configured to communicate the data as a low voltage differential data signal.

However, please refer to the rejection of Claims 13 and 35 for explanation as to why it would have been obvious to implement the system of Schutte as a differential signaling system. If the system of Schutte has been implemented as a differential signaling system then both the clock and data signal lines would be differential signal lines as claimed in the present application.

Art Unit: 2111

Claim 23 is rejected under 35 U.S.C. 103(a) as being unpatentable over Schutte U.S. Patent No. 6,092,138 in view of Baker et al. U.S. Patent No. 7,168,00.

Per Claim 23, Schutte discloses the multiple integrated circuit control implemented within an electronic apparatus, but does not distinctly disclose the electronic apparatus as being an application-specific integrated circuit (ASIC).

- However, Baker discloses an I2C bus master embedded within an ASIC device (column 3 lines 57-61, column 4 lines 23-37, figures 1 and 2).

It would have been obvious to one having ordinary skill in the art at the time of the applicants claimed invention to combine the multiple integrated circuit control of Schutte into an ASIC device disclosed by Baker in order to create an ASIC device with an embedded I2C bus master. The combination would have been obvious in order to reduce production costs.

Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Schutte U.S. Patent No. 6,092,138 in view of Oppedahl, U.S. Patent No. 5,500,861.

Per Claim 36, Schutte discloses:

- communicating a data transaction start indication from the multiple integrated circuit control to the integrated circuits (column 5 lines 49-67, column 6 lines 11-28, figure 1 and 2 – start condition);
- communicating a unique target identifier to initiate the data transaction with an integrated circuit that is identified by the unique target identifier (column 6 lines 11-16, figure 1 – address of a “slave” station);

Art Unit: 2111

- communicating control data from the multiple integrated circuit control to define the data transaction with the identified integrated circuit (column 6 lines 11-16 – read/write bit);
- communicating the data between the multiple integrated circuit control and the identified integrated circuit, wherein the multiple integrated circuit control is a data sending device and the identified integrated circuit is a data receiving device in an event that the data is communicated from the multiple integrated circuit control to the identified integrated circuit, further wherein the multiple integrated circuit control is the data receiving device and the identified integrated circuit is the data sending device in an event that the data is communicated from the identified integrated circuit to the multiple integrated circuit control (column 6 lines 11-24, figure 1 - the master station utilizes the read/write bit to indicate what type of data communication will take place; any of the stations can act as a master and when acting as the master can communicate both read and write transactions with any of the other stations);
- communicating a data acknowledgement from the data receiving device to the data sending device to indicate receipt of the data and the data parity bit (column 6 lines 35-50, figure 1 – acknowledge bit);
- and communicating a data transaction stop indication from the data sending device to the data receiving device to indicate receipt of the data acknowledgement (column 6 lines 29-35, figures 1-5).

Schutte does not disclose: a control parity bit or a data parity bit.

- However, Oppendahl discloses both control parity bits and data parity bits (column 4 lines 51-56, column 5 lines 9-16).

It would have been obvious to one having ordinary skill in the art at the time of the applicants claimed invention to incorporate the parity bits of Oppendahl into

Art Unit: 2111

the system of Schutte. The combination would have obvious because it adds an extra level of data integrity to the system which is something that any system designer would welcome assuming that the resources to do so are available.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Brian T. Misiura whose telephone number is (571) 272-0889. The examiner can normally be reached on M-F 8:00-4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mark Rinehart can be reached on (571) 272-3632. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Brian Misiura

4/13/2007



Glenn A. Auve
Primary Patent Examiner
Technology Center 2100